

Power Product Line

Z-REC™ RECTIFIERS AND ZERO-RECOVERY® RECTIFIERS

	V _{RRM} (V)	I _{F(AVG)} (A)	V _{F(TJ=25°C)}		V _{F(TJ=175°C)}		T _{J(Max)}	Package Type	
			Typ	Max	Typ	Max			
CSD01060A	600	1	1.6	1.8	2.0	2.4	175°C	TO-220-2	See Fig. 1
CSD01060E	600	1	1.6	1.8	2.0	2.4	175°C	DPAK	See Fig. 2
C3D02060A	600	2	1.5	1.7	1.8	2.4	175°C	TO-220-2	See Fig. 1
C3D02060E	600	2	1.5	1.7	1.8	2.4	175°C	DPAK	See Fig. 2
C3D02060F	600	2	1.5	1.7	1.8	2.4	175°C	Full-Pak	See Fig. 5
C3D03060A	600	3	1.5	1.7	1.8	2.4	175°C	TO-220-2	See Fig. 1
C3D03060E	600	3	1.5	1.7	1.8	2.4	175°C	DPAK	See Fig. 2
C3D03060F	600	3	1.5	1.7	1.8	2.4	175°C	Full-Pak	See Fig. 5
C3D04060A	600	4	1.5	1.7	1.8	2.4	175°C	TO-220-2	See Fig. 1
C3D04060E	600	4	1.5	1.7	1.8	2.4	175°C	DPAK	See Fig. 2
C3D04060F	600	4	1.5	1.7	1.8	2.4	175°C	Full-Pak	See Fig. 5
C3D06060A	600	6	1.6	1.8	1.9	2.4	175°C	TO-220-2	See Fig. 1
C3D06060G	600	6	1.6	1.8	1.9	2.4	175°C	D ² PAK	See Fig. 3
C3D08060A	600	8	1.6	1.8	1.9	2.4	175°C	TO-220-2	See Fig. 1
C3D08060G	600	8	1.6	1.8	1.9	2.4	175°C	D ² PAK	See Fig. 3
C3D10060A	600	10	1.5	1.8	2.0	2.4	175°C	TO-220-2	See Fig. 1
C3D10060G	600	10	1.5	1.8	2.0	2.4	175°C	D ² PAK	See Fig. 3
C3D20060D	600	20	1.5	1.8	2.0	2.4	175°C	TO-247-3	See Fig. 4
C2D05120A	1200	5	1.6	1.8	2.6	3.0	175°C	TO-220-2	See Fig. 1
C2D10120A	1200	10	1.6	1.8	2.5	3.0	175°C	TO-220-2	See Fig. 1
C2D10120D	1200	10	1.6	1.8	2.6	3.0	175°C	TO-247-3	See Fig. 4
C2D20120D	1200	20	1.6	1.8	2.5	3.0	175°C	TO-247-3	See Fig. 4




Fig. 1 TO-220-2



Fig. 2 DPAK



Fig. 3 D²PAK




Fig. 4 TO-247-3




Fig. 5 Full-Pak